



## BRX Elite Full Syn dexos1™

BRX Elite Full Syn dexos1™ is formulated from select synthetic base stocks and advanced additive technology approved by General Motors to meet their new Global Motor Oil Specification. BRX Elite Full Syn dexos1™ provides aggressive resistance to sludge formation and varnish deposits during stop-and-go driving. Premium synthetic formulation delivers excellent oxidation stability and low volatility properties, resulting in reduced oil consumption between services. BRX Elite Full Syn dexos1™ is recommended for turbo-charged or naturally aspirated gasoline-powered and flex-fuel passenger cars, hybrid vehicles, light trucks, and sport utility vehicles. It exceeds new car warranty requirements as defined by API SN PLUS Resource Conserving (RC), ILSAC GF-5. Always consult your owner's manual for recommendations.

### VEHICLE BENEFITS

- Optimum wear protection as defined by GM's Opel RNT camshaft test
- Optimum fuel economy
- Excellent low-temperature performance for cold starts
- Protects vehicle emission systems
- Advanced shear stability and low volatility properties support extended service intervals
- Improved LSPI protection
- Improved wear performance
- Maximum Engine Protection

### PRODUCT FEATURES

- Exceeds API SN PLUS Resource Conserving (RC), ILSAC GF-5 performance standards
- Approved and licensed for GM Warranty Service as a dexos1™ – Gen 2 motor oil
- Formulated with 100% synthetic base stocks for maximum resistance to thermal breakdown
- Optimum oxidation stability and volatility properties reduce oil consumption between services
- Advanced additive technology provides added resistance to sludge formation and piston deposits
- Meets service fill requirements of JAMA member OEMs

### APPLICATIONS

- Full Synthetic Motor Oil
- Exceeds API SN PLUS Resource Conserving (RC), ILSAC GF-5 Standards
- Meets the stringent standards of dexos1™ – Gen 2
- Ford WSS-M2C946-B1 (5W-30)  
Ford WSS-M2C947-B1 (0W-20)
- Chrysler; MS-6395 (Revision S)

BRX Elite Full Syn dexos1™ Typical Physical Properties			
Property	Test Method	0W-20	5W-30
API Service		SN PLUS RC	SN PLUS RC
Density@15°C, g/cm <sup>3</sup>	ASTM D4052	0.8474	0.8520
Viscosity @ 40°C, cSt	ASTM D445	46.1	55.0
Viscosity @ 100°C, cSt	ASTM D445	8.8	9.8
Viscosity Index	ASTM D2270	174	165
Flash Point, °C (°F)	ASTM D93	210°C (410°F)	208°C (406°F)
Pour Point, °C (°F)	ASTM D97	-45°C (-49°F)	-45°C (-49°F)
CCS, cP	ASTM D5293	5,010 @ -35°C	3,750 @ -30°C
MRV, cP	ASTM D4684	29,900 @ -40°C	11,900 @ -35°C
HTHS, @150°C, cP	ASTM D4683	2.7	2.9
TBN, mg KOH/g	ASTM D2896	7.8	8.2
Noack Volatility, wt%	ASTM D5800	11	9
Zinc, wt%	ASTM D6481	0.085	0.085

*Minor variations in typical physical properties may occur from normal manufacturing processes*

#### DISTRIBUTED BY:

Calumet Branded Products, LLC  
2780 Waterfront Pkwy. E. Dr., Suite 200  
Indianapolis, IN 46214  
Technical Services: 317-328-5660  
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.