



# PRODUCT DATA SHEET



---

## NO-TOX<sup>®</sup> FOOD GRADE DRY PTFE SPRAY

**No-Tox Food Grade Dry PTFE Spray** is a multipurpose, convenient-to-use, dry-film lubricant that is NSF H1 registered for use where incidental food contact may occur. **No-Tox Food Grade Dry PTFE Spray** is fortified with PTFE lubricating solids to provide a clean, durable and long-lasting dry film for use in the “clean industries” where molybdenum disulfide (commonly known as Moly) and graphite are not permitted. **No-Tox Food Grade Dry PTFE Spray** is non-toxic and manufactured from FDA compliant ingredients.

### *Applications*

- ◆ For multipurpose, dry-film lubrication of metal surfaces in the “clean” industries where other solid lubricants such as molybdenum disulfide or graphite cannot be used
- ◆ For lubricating bearings, slide ways, conveyors, chains, cams and hinges

### *Features and Benefits*

- ◆ NSF H1 registered                      Use where incidental food contact may occur.
- ◆ Superior dry-film lubrication      Durable white film does not easily transfer during operation.
- ◆ Solid lubricants                         Fortified with PTFE to provide a light, non-toxic layer of lubrication to reduce friction and prolong component life.
- ◆ User friendly                             Will not affect plastic or painted surfaces. Non-toxic, non-corrosive and non-irritating.
- ◆ Waterproof and solvent resistance      Suitable for wet and solvent environments.

### *General Description*

**No-Tox Food Grade Dry PTFE Spray** is an outstanding dry-film lubricant in an aerosol package for convenient application. **No-Tox Food Grade Dry PTFE Spray**, formulated with the highest quality ingredients, meets NSF H1 and FDA requirements for materials that may have incidental contact with food as defined under Title 21 CFR 178.3570. It is Kosher and Pareve approved, as well as Halal certified.

### *Product No. 301055*

# NO-TOX<sup>®</sup> FOOD GRADE DRY PTFE SPRAY

## TYPICAL PROPERTIES

|                               |                      |
|-------------------------------|----------------------|
| <b><u>Product No.</u></b>     | <b><u>301055</u></b> |
| <b><u>Old Product No.</u></b> | <b><u>61710</u></b>  |
| Lubricating Solids Type       | PTFE                 |
| Useful Temperature Range      |                      |
| °C                            | -200 to 250          |
| (°F)                          | -328 to 480          |
| Appearance                    | Dry Film             |
| Color                         | White                |

**Caution:** *Use in a well-ventilated space.*

*Product is flammable and should be used with appropriate caution.*

*Do not spray on a hot surface or in proximity to flames or open fire.*

*Do not puncture or incinerate container, even when empty.*

*Always wear safety glasses when using this product.*

*Keep container away from heat.*

***To clean nozzle, invert aerosol can and depress nozzle after use.***

Use in the manufacturing process only. For food plant and other industrial uses. Avoid direct addition to food during use of product. Use as recommended by a company representative. Use with minimum application necessary to accomplish desired technical effect. Remove excess with clean cloth. To be used where contact of the lubricant with food is incidental at a level of the product not to exceed 10 ppm.