



PRODUCT DATA SHEET



SUPER DOT 4 BRAKE FLUID

Super DOT 4 Brake Fluid exceeds FMVSS / CMVSS 116 DOT 4, SAE J1703, SAE J1704 and ISO 4925 brake fluid specifications. **Super DOT 4 Brake Fluid** mixes with all fluids meeting DOT 3 and DOT 4 specifications. **Super DOT 4 Brake Fluid** is for use in all drum or disc brake systems and hydraulic clutches, except systems using mineral-based fluids (LHM).

Dry Boiling Point: 272°C (522°F)

Wet Boiling Point: 170°C (337°F).

Applications

- ◆ When DOT 3 or DOT 4 product is specified for hydraulic brake systems

Features and Benefits

- | | |
|------------------------|--|
| ◆ High vapor point | Resists vapor formation to minimize the potential for “vapor lock” and the subsequent loss of braking power. |
| ◆ High boiling point | Eliminates brake fade for superior performance. |
| ◆ High compatibility | Compatible with all seal materials normally used in brake systems. |
| ◆ Corrosion protection | Special formulation with inhibitors against rust and chloride corrosion. |

Application Instructions

Follow vehicle manufacturer’s recommendations when adding brake fluid. Keep brake fluid clean and dry. Contamination with dirt, water, petroleum products or other materials may result in brake failure or costly repairs. Store brake fluid only in its original container. Keep container clean and tightly closed to prevent absorption of moisture.

For best results drain and replace the brake fluid once a year. Flush and refill system with fresh **Bel-Ray Super DOT 4 Brake Fluid**. Bleed the hydraulic system as recommended by the manufacturer. Check and replace damaged seals and dust protectors if needed. Dispose of empty containers in a responsible manner.

Product No. 301292 (Old Product No. 99480)