

## V-TWIN MINERAL ENGINE OIL

V-Twin Mineral Engine Oil is a value priced, multi-grade 4-stroke petroleum engine oil formulated for V-Twin engines. It is formulated with high Viscosity Index and low volatility petroleum base oils.

V-Twin Mineral Engine Oil provides shear and oxidation stability and deposit control for quality lubrication performance and engine protection. Specific Bel-Ray anti-wear chemistry means engines last longer and are more reliable with added wear protection to increase bearing life. Equally suitable for air or liquid cooled engines, V-Twin Mineral Engine Oil meets or exceeds V-Twin requirements and WILL NOT void warranties.



### APPLICATIONS

- Use in all V-Twin engines where economical protection is desired

### PRODUCT FEATURES

- Quality engine protection
- Low volatility base oils
- Superior deposit control
- Increased reliability
- Economical protection
- JASO MA2 wet clutch performance

### BENEFITS

- Exclusive Bel-Ray anti-wear chemistry reduces bearing and valve train wear and keeps pistons and rings from scuffing.
- Minimize oil consumption.
- Cleans deposits and reduces sludge and varnishes.
- It lowers temperatures and minimizes deposit formation for cleaner and cooler running engine.
- Bel-Ray's additive chemistry, high Viscosity Index, low volatility petroleum base oils and oxidation stability provide added wear protection for increased engine reliability.
- Provides excellent low cost lubrication performance, engine protection and reliable all-season use

#### DISTRIBUTED BY:

Calumet Branded Products, LLC  
2780 Waterfront Pkwy. E. Dr., Suite 200  
Indianapolis, IN 46214  
Technical Services: 317-328-5660  
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

© 2020 Calumet Specialty Products, LLC. All Rights Reserved.

11/23/2021



Typical Physical Properties		
Property	Test Method	20W-50
API Service		SN (claimed)
JASO Classification		MA2
Density@15°C, g/cm3	ASTM D4052	0.8844
Viscosity @ 40°C, cSt	ASTM D445	150.2
Viscosity @ 100°C, cSt	ASTM D445	16.8
Viscosity Index	ASTM D2270	120
Cold Crank Simulator, cP	ASTM D5293	7942
Flash Point, °C (°F)	ASTM D92	239 (462)
Pour Point, °C (°F)	ASTM D97	-27 (-17)

**DISTRIBUTED BY:**  
 Calumet Branded Products, LLC  
 2780 Waterfront Pkwy. E. Dr., Suite 200  
 Indianapolis, IN 46214  
 Technical Services: 317-328-5660  
[www.belray.com](http://www.belray.com)

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

© 2020 Calumet Specialty Products, LLC. All Rights Reserved.

11/23/2021