



## BRX-HM High Mileage Motor Oil

Bel-Ray® BRX-HM High Mileage Motor Oil is specially formulated from a proprietary combination of premium synthetic-blend base stocks and advanced additive technology to deliver superior protection to older, higher mileage vehicles. Bel-Ray® BRX-HM High Mileage features a state-of-the-art additive system that contains active cleaning agents that maintains performance in older engines and that help to rejuvenate seals and gaskets. Recommended for turbo-charged or naturally aspirated gasoline-powered passenger cars, light trucks and sport utility vehicles with 75,000 odometer miles or more. It exceeds new car warranty requirements as defined by the API SP Resource Conserving and ILSAC GF-6A engine oil specifications. Always consult your owner's manual for recommendations.

### APPLICATIONS

- Licensed under API SP Resource Conserving and ILSAC GF-6A; backwards compatible with all prior API and ILSAC specs
- Ford WSS-M2C960-A (5W-20), Ford WSS-M2C961-A (5W-30)
- Chrysler MS-6395
- GM 6094M

### PRODUCT FEATURES

- Exceeds API SP Resource Conserving and ILSAC GF-6A performance standards
- Formulated with premium synthetic-blend base stocks for added resistance to thermal breakdown
- Special seal conditioners revitalize and recondition shrunken and slightly worn engine seals
- Improved oxidation stability and volatility properties reduce oil consumption between services
- Advanced additive technology helps mature engine maintain cleanliness, and protects against sludge and piston deposits
- Meets service fill requirements of JAMA member OEMs

### BENEFITS

- Great wear protection for critical engine components in older vehicles
- Improved oil consumption compared to typical engine oils
- Improved fuel economy
- Great low-temperature performance
- Maintains engine protection under severe operating conditions
- Protects vehicle emission systems
- Improved wear performance

#### DISTRIBUTED BY:

Calumet Branded Products, LLC  
2780 Waterfront Pkwy. E. Dr., Suite 200  
Indianapolis, IN 46214  
Technical Services: 317-328-5660  
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

© 2020 Calumet Specialty Products, LLC. All Rights Reserved.

3/2/2021



Typical Physical Properties				
Property	Test Method	5W-20	5W-30	10W-30
API Service		SP	SP	SP
Density@15°C, g/cm <sup>3</sup>	ASTM D4052	0.860	0.857	0.860
Viscosity @ 40°C, cSt	ASTM D445	51	63	68
Viscosity @ 100°C, cSt	ASTM D445	8.6	10.6	10.9
Viscosity Index	ASTM D2270	145	155	150
Flash Point, °C (°F)	ASTM D92	227 (440)	224 (436)	229 (444)
Pour Point, °C (°F)	ASTM D97	-45 (-49)	-48 (-54)	-48 (-54)
Cold Crank Simulator, cP	ASTM D5293	6,018 @-30°C	6,340 @-30°C	4,559 @-25°C
TBN, mg KOH	ASTM D2896	7.7	7.6	7.7
HTHS, @150°C, cP	ASTM D5481	2.7	3.1	3.2

**DISTRIBUTED BY:**  
 Calumet Branded Products, LLC  
 2780 Waterfront Pkwy. E. Dr., Suite 200  
 Indianapolis, IN 46214  
 Technical Services: 317-328-5660  
[www.belray.com](http://www.belray.com)

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

© 2020 Calumet Specialty Products, LLC. All Rights Reserved.

3/2/2021