



Hyperion Synthetic Blend Engine Oil

Bel-Ray® Hyperion Synthetic Blend Engine Oil is formulated for use in high-speed four-stroke cycle diesel engines designed to meet 2017 model year on-highway and Tier 4 non-road exhaust emission standards, as well as for previous model year diesel engines. This oil is formulated for use in all applications with diesel fuels ranging in sulfur content up to 500 ppm. The full synthetic base oils used in Hyperion Elite Synthetic provide enhanced lubricity and cold-flow, and improved resistance to high-temperature degradation. The advanced additive package in this formulation reduces viscosity loss due to shear, and oil aeration. Also, the advanced, low-ash formulation provides protection against catalyst poisoning and particulate filter blocking, while preventing deposit formation and soot-related viscosity increase.

APPLICATIONS

- **Warranty compliant for all vehicles requiring a licensed API CK-4 diesel engine oil**
- Licensed under API CK-4/SN specification; backwards compatible with all prior API diesel specs
- Cummins CES20086
- Detroit Diesel 93K222
- Ford WSS-M2C171
- Mack EOS-4.5
- MTU 2
- Renault RLD-3
- Volvo VDS-4.5

PRODUCT FEATURES

- Exceeds API CK-4/SN performance standards
- Formulated with synthetic base stocks for maximum resistance to thermal breakdown
- Optimum oxidation stability and volatility properties reduce oil consumption between services
- Advanced additive technology provides added resistance to sludge formation and piston deposits
- Carries API license for diesel (CK-4) and gasoline (SN)** engine use

BENEFITS

- Outstanding wear protection as established in API CK-4 specification
- Optimum fuel economy
- Enhanced low-temperature performance for cold starts
- Improved protection for exhaust SCR catalysts and particulate filters
- Advanced shear stability and low volatility properties support extended service intervals
- Excellent overall engine protection

**API SN license applies to SAE 15W-40, only

DISTRIBUTED BY:

Calumet Branded Products, LLC
2780 Waterfront Pkwy. E. Dr., Suite 200
Indianapolis, IN 46214
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

© 2020 Calumet Specialty Products, LLC. All Rights Reserved.

4/8/2021



Typical Physical Properties			
Property	Test Method	10W-30	15W-40
API Service		CK-4	CK-4/SN
Density@15°C, g/cm3	ASTM D4052	0.867	0.870
Viscosity @ 40°C, cSt	ASTM D445	81.3	110.5
Viscosity @ 100°C, cSt	ASTM D445	11.9	14.8
Viscosity Index	ASTM D2270	140	139
Flash Point, °C (°F)	ASTM D92	236 (456)	229 (444)
Pour Point, °C (°F)	ASTM D97	-48 (-54)	-48 (-54)
Cold Crank Simulator, cP	ASTM D5293	6,640 @-25°C	5,100 @-20°C
TBN, mg KOH	ASTM D2896	9.6	10
Sulfated Ash, wt%	ASTM D874	1.0	0.98

DISTRIBUTED BY:
 Calumet Branded Products, LLC
 2780 Waterfront Pkwy. E. Dr., Suite 200
 Indianapolis, IN 46214
 Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

© 2020 Calumet Specialty Products, LLC. All Rights Reserved.

4/8/2021