



PRODUCT DATA SHEET



NO-TOX[®] FOOD GRADE SILICONE LUBRICANT SPRAY

No-Tox Food Grade Silicone Lubricant Spray, commonly known as No-Tox Silicone Lube, is a high viscosity, pearlescent, smooth, tacky, and waterproof silicone fluid in an aerosol package. **No-Tox Food Grade Silicone Lubricant Spray** is NSF H1 registered for use where incidental food contact may occur and is compatible with most seal materials. It is resistant to many reactive chemicals that may be encountered in “clean” industries such as food and beverage, pharmaceuticals and personal care plants. **No-Tox Food Grade Silicone Lubricant Spray** is ideal for use as a general lubricant, cleaner and preservative.

Applications

- ◆ Widely used in food and poultry plants operating under the Federal Meat and Poultry Products Inspection Program’s Food Safety and Inspection Service (FSIS)

Features and Benefits

- | | |
|------------------------------|---|
| ◆ NSF H1 registered | Use where incidental food contact may occur. |
| ◆ Compliances | Kosher and Pareve approved. Halal certified. |
| ◆ Bacteriological protection | Effectively inhibits the growth of certain bacteria, yeast and mold in the lubricant. |
| ◆ Chemically inert | Will not affect rubber, plastic or metal. |
| ◆ Chemically resistant | Unaffected by mild acids, alkalis, alcohol and glycol. |
| ◆ Waterproof | Ideal for wet conditions and water displacing. |

General Description

No-Tox Food Grade Silicone Lubricant Spray is a silicone fluid for use in the food, beverage, pharmaceutical, personal care products, printing, electric, electronic and other industries where its retentive, water repellent and non-gumming characteristics make it a universal-type lubricant. **No-Tox Food Grade Silicone Lubricant Spray**, formulated with the highest quality ingredients, meets NSF H1 and FDA requirements for materials that may have incidental contact with food as defined under Title 21 CFR, 178.3570. It is Kosher and Pareve approved, as well as Halal certified.

Product No. 300879

NO-TOX[®] FOOD GRADE SILICONE LUBRICANT SPRAY
TYPICAL PROPERTIES OF CONCENTRATE

<u>Product No.</u>	<u>300879</u>
<u>Old Product No.</u>	<u>61780</u>
Viscosity (Base Fluid), ASTM D445	
@ 25°C, cSt	425
@ 40°C, cSt	326
@ 100°C, cSt	139
Base Fluid Type	Dimethyl Silicone
Flash Point, ASTM D92	
°C	>321
(°F)	(>610)
Color	Off-white

Caution: *Use in a well-ventilated space.*

Product is flammable and should be used with appropriate caution.

Do not spray on a hot surface or in proximity to flames or open fire.

Do not puncture or incinerate container, even when empty.

Always wear safety glasses when using this product.

Keep container away from heat.

Use in the manufacturing process only. For food plant and other industrial uses. Avoid direct addition to food during use of product. Use as recommended by a company representative. Use with minimum application necessary to accomplish desired technical effect. Remove excess with clean cloth. To be used where contact of the lubricant with food is incidental at a level of the product not to exceed 10 ppm.