



Saw Guide 100

Bel-Ray® Saw Guide 100 is designed with premium base stocks and additive system that reduces friction between saw and guide components. They are designed to be used for lubricating arbor bearings and saw guide systems.

Bel-Ray Saw Guide 100 contains rust inhibitors and a tackifier to resist slinging.

EQUIPMENT BENEFITS

- Excellent wash-off resistance
- High tackiness to stay on saws and guides
- Non-corrosive & non-staining
- Good low temperature properties

PRODUCT FEATURES

- Potent Antiwear additive system
- Control of Stray Mist
- Oil Consumption Control
- Pitch Deposit Control
- Excellent Rust and Corrosion Protection

APPLICATIONS

- Edger gangsaws
- Trimmers
- Bandmills
- Older sawmill applications where circular saws are used
- Smaller portable circular or bandmills
- Arbor bearings

Saw Guide 100 Typical Physical Properties		
Property	Test Method	100
Density@15°C, g/cm ³	ASTM D4052	0.877
API Gravity @ 60°F	ASTM D4052	29.8
Viscosity @ 40°C, cSt	ASTM D445	100.0
Viscosity @ 100°C, cSt	ASTM D445	11.4
Viscosity Index	ASTM D2270	100
Flash Point, °C (°F)	ASTM D92	216 (421)
Pour Point, °C (°F)	ASTM D97	-9 (16)
Pounds per Gallon	ASTM D1250	7.31

Minor variations in typical physical properties may occur from normal manufacturing processes

DISTRIBUTED BY:

Calumet Branded Products, LLC
2780 Waterfront Pkwy. E. Dr., Suite 200
Indianapolis, IN 46214
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.