

BRX™ Elite Full Synthetic dexos™1 Gen 3 Motor Oils

PRODUCT DESCRIPTION

Bel-Ray® BRX™ Elite Full Synthetic dexos™1 Gen 3 Motor Oils are formulated from select synthetic base stocks and advanced additive technology approved by General Motors to meet their current motor oil specification. The advanced additive package also provides unsurpassed protection against LSPI (Low Speed Pre-Ignition) for modern Gasoline Direct Injection (GDI) engines. The premium synthetic formulation delivers excellent oxidation stability and low volatility properties for maximizing oil drain intervals and resulting in reduced oil consumption between services. BRX Elite Full Synthetic dexos™1 Gen 3 motor oils provide aggressive resistance to sludge formation and varnish deposits during stop-and-go driving.

PRODUCT FEATURES and BENEFITS

- Optimized with low coefficient of friction for increased fuel efficiency and engine power output
- Formulated with anti-wear additives to provide maximum engine wear protection in harsh and demanding applications
- Superior oxidative stability provides resistance to high-temperature thermal breakdown and minimizes engine wear
- Excellent low-temperature performance protects crucial components during cold starts and operating environments
- Improved Low Speed Pre-Ignition (LSPI) protection to provide protection to engine components and maximize engine life
- Advanced shear stability and low volatility properties to support extended service intervals

APPLICATIONS

Bel-Ray BRX Elite Full Synthetic dexos™1 Gen 3 Motor Oils are recommended for gasoline engines in passenger cars, SUVs, light vans and light trucks. The applications include GDI, multi-valve fuel injected, carbureted, turbocharged, and supercharged engines, and those needing to meet dexos™1 Gen 3 requirements.

SPECIFICATIONS and APPROVALS

	0W-20	5W-30
API SQ Resource Conserving*	X	X
ILSAC GF-7A*	X	X
dexos™1 Gen 3	X	X
Chrysler MS-6395	●	●
Ford WSS-M2C972-A1	●	
Ford WSS-M2C971-A1		●

X - Formally licensed / registered

● - Recommended for use / meets requirements

*Backwards compatible with prior requirements

DISTRIBUTED BY:

Calumet Branded Products, LLC
1060 N Capitol Ave
Suite 6-401
Indianapolis, IN 46204
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name in use and whether there is any infringement of patents is the sole responsibility of the user.

All trademarks are owned by one or more affiliates within the Calumet, Inc. organization, unless otherwise specified.

© 2025 Calumet, Inc.

4/29/2025

PRODUCT DATA

Typical Properties			
Property	Test Method	0W-20	5W-30
Viscosity @ 40°C, cSt	ASTM D445	45.9	55.1
Viscosity @ 100°C, cSt	ASTM D445	8.6	9.9
Viscosity Index	ASTM D2270	168	168
Cold Crank Simulator, cP	ASTM D5293	4,912 @ -35°C	3,744 @ -30°C
HTHS @ 150°C, cP	ASTM D5481	2.6	2.9
Pour Point, °C (°F)	ASTM D97	-42 (-44)	-45 (-49)
Flash Point, °C (°F)	ASTM D92	232 (450)	226 (440)
Density @ 15°C, g/mL	ASTM D4052	0.848	0.846

dexosTM1 is a registered trademark of the General Motors Corporation

HEALTH and SAFETY

Health and safety recommendations for products can be found on the Safety Data Sheet (SDS) at www.belray.com