

## BRX™ Elite Full Synthetic Ultra-Low Viscosity

### PRODUCT DESCRIPTION

Bel-Ray® BRX™ Elite Full Synthetic Ultra-Low Viscosity Motor Oils are formulated from select full-synthetic base stocks and advanced additive technology to deliver trusted engine protection and peak vehicle performance. Bel-Ray BRX Elite Full Synthetic Ultra-Low Viscosity Motor Oils provide aggressive resistance to sludge formation and varnish deposits during stop-and-go driving. The advanced additive package also provides unsurpassed protection against LSPI (Low Speed Pre-Ignition) for modern Gasoline Direct Injection (GDI) engines. The premium synthetic formulation delivers excellent oxidation stability and low volatility properties for maximizing oil drain intervals and resulting in reduced oil consumption between services.

### PRODUCT FEATURES and BENEFITS

- Optimized with low coefficient of friction for increased fuel efficiency and engine power output
- Formulated with anti-wear additives to provide maximum engine wear protection in harsh and demanding applications
- Superior oxidative stability provides resistance to high-temperature thermal breakdown and minimizes engine wear
- Excellent low-temperature performance protects crucial components during cold starts and operating environments
- Improved Low Speed Pre-Ignition (LSPI) protection to provide protection to engine components and maximize engine life
- Advanced shear stability and low volatility properties to support extended service intervals

### APPLICATIONS

Bel-Ray BRX Elite Full Synthetic Ultra-Low Viscosity Motor Oils are recommended for gasoline engines in passenger cars, SUVs, light vans and light trucks. The applications include GDI, multi-valve fuel injected, turbocharged, and supercharged engines.

### SPECIFICATIONS and APPROVALS

	0W-16
API SQ Resource Conserving*	X
ILSAC GF-7B*	X

X - Formally licensed / registered

- - Recommended for use / meets requirements

\*Backwards compatible with ILSAC GF-6B requirements

# TECHNICAL DATA SHEET



## PRODUCT DATA

Typical Properties		
Property	Test Method	0W-16
Viscosity @ 40°C, cSt	ASTM D445	37.3
Viscosity @ 100°C, cSt	ASTM D445	7.3
Viscosity Index	ASTM D2270	165
Cold Crank Simulator, cP	ASTM D5293	5,024 @ -35°C
HTHS @ 150°C, cP	ASTM D5481	2.4
Pour Point, °C (°F)	ASTM D97	-45 (-49)
Flash Point, °C (°F)	ASTM D92	246 (474)
Density @ 15°C, g/mL	ASTM D4052	0.846

## HEALTH and SAFETY

Health and safety recommendations for products can be found on the Safety Data Sheet (SDS) at [www.belray.com](http://www.belray.com)

### DISTRIBUTED BY:

Calumet Branded Products, LLC  
1060 N Capitol Ave  
Suite 6-401  
Indianapolis, IN 46204  
Technical Services: 317-328-5660  
[www.belray.com](http://www.belray.com)

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name in use and whether there is any infringement of patents is the sole responsibility of the user.

All trademarks are owned by one or more affiliates within the Calumet, Inc. organization, unless otherwise specified.

© 2025 Calumet, Inc.

4/29/2025