



No-Tox[®] Food Grade Multipurpose Lubricant Spray

PRODUCT DESCRIPTION

Bel-Ray[®] No-Tox[®] Food Grade Multipurpose Lubricant Spray, commonly known as No-Tox Multipurpose Lube Aerosol, is a versatile, general-purpose lubricant designed for all types of equipment found in the “clean” industries such as food, beverage, pharmaceutical and personal care. No-Tox Food Grade Multipurpose Lubricant Spray is a food grade lubricant that cleans, lubricates, and preserves, and is ideal for preventing rust and displacing water from equipment parts.

No-Tox Food Grade Multipurpose Lubricant Spray, formulated with the highest quality ingredients, meets NSF H1 and FDA requirements for materials that may have incidental contact with food as defined under Title 21 CFR, 178.3570. It is Kosher and Pareve approved, as well as Halal certified. ISO 21469 certified food grade lubricant.



Nonfood Compounds
H1 Registered,
ISO 21469 Certified

PRODUCT FEATURES

- NSF H1 registered and ISO 21469 certified
- Bacteriological protection
- Kosher and Pareve approved
- Halal certified
- Anti-wear protection
- Rust and oxidation prevention
- Excellent penetration properties
- Tacky and non-drip

BENEFITS

- Use where incidental food contact may occur.
- Effectively inhibits the growth of certain bacteria, yeast, and mold in the lubricant.
- Longer service life.
- Reduces friction and wear.
- Creeps and penetrates deeply into any metal parts.
- Provides superior adhesion to metal.

DISTRIBUTED BY:
Calumet Branded Products, LLC
1060 N Capitol Ave
Suite 6-401
Indianapolis, IN 46204
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name in use and whether there is any infringement of patents is the sole responsibility of the user.

All trademarks are owned by one or more affiliates within the Calumet, Inc. organization, unless otherwise specified.

© 2026 Calumet, Inc.

6/11/2026



APPLICATIONS

Widely used in food and poultry plants operating under the Federal Meat and Poultry Products Inspection Program's Food Safety and Inspection Service (FSIS).

PRODUCT DATA

Typical Properties		
Property	Test Method	ISO 100
Viscosity @ 40°C (cSt)	ASTM D445	99.4
Viscosity @ 100°C (cSt)	ASTM D445	11.2
Viscosity Index	ASTM D2270	98
4-Ball Wear Test, @ 1200 rpm, 40 kgf, 60 min, 75°C Scar Diameter (mm)	ASTM D4172	0.48
Corrosion Preventive Properties	ASTM D1743	Pass
Color		Water-White

HEALTH and SAFETY

Health and safety recommendations for products can be found on the Safety Data Sheet (SDS) at www.belray.com