



Rust Preventative

PRODUCT DESCRIPTION

Bel-Ray® Rust Preventative is a premium performance product which provides effect rust preventative films on the internal surfaces of machinery. It is particularly suitable as lubricants for diesel and gasoline engines. The oils displace water from metal surfaces and form strong water resistant films on the metal surfaces to prevent rust and corrosion. Bel-Ray Rust Preventative absorbs the water in systems into a water-in-oil emulsion so that the contact surfaces of the machinery still get satisfactory lubrication. Their high level of chemical stability and their anti-wear and detergent properties make them suitable as high quality short-term lubricants.

PRODUCT FEATURES

- Excellent rust and corrosion protection.
- Effective antiwear properties
- Dual purpose lubricant / rust-preventative nature

BENEFITS

- High level protection against rust during seasonal lay-ups
- Reduced clean-up time required to place equipment back into production
- Displaces water from metal surfaces and form tenacious protective films
- Effective Anti-Wear Properties Protects equipment against wear
- Reduced cost and time for run-in, testing or adjustment procedures
- Eliminates unnecessary flushing and draining steps

APPLICATIONS

- Eaton Vickers 35VQ25A Pump M-2950-S, & I-286-S
- DIN 51524 Part 2 (HLP)
- Eaton Brochure 03-401-2010
- Parker Denison HF-0
- Fives Cincinnati P-68
- Fives Cincinnati P-69
- Fives Cincinnati P-70
- Parker Hannifin France HF-0 Approved (Hybrid T6H20C Pump Test)

DISTRIBUTED BY:

Calumet Branded Products, LLC
1060 N Capitol Ave
Suite 6-401
Indianapolis, IN 46204
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name in use and whether there is any infringement of patents is the sole responsibility of the user.

All trademarks are owned by one or more affiliates within the Calumet, Inc. organization, unless otherwise specified.

© 2026 Calumet, Inc.

4/30/2026



PRODUCT DATA

Typical Properties		
Property	Test Method	
API Gravity @ 60°F	ASTM D4052	29.6
Density @ 15°C (g/mL)	ASTM D4052	0.879
Viscosity @ 40°C (cSt)	ASTM D445	72.98
Viscosity @ 100°C (cSt)	ASTM D445	9.54
Viscosity Index	ASTM D2270	109
Flash Point, °C (°F)	ASTM D92	196 (385)
Pour Point, °C (°F)	ASTM D97	-12 (-10)
Zinc (Wt %)	ASTM D6481	0.115
Pounds per Gallon	ASTM D1250	7.32

HEALTH and SAFETY

Health and safety recommendations for products can be found on the Safety Data Sheet (SDS) at www.belray.com

DISTRIBUTED BY:
 Calumet Branded Products, LLC
 1060 N Capitol Ave
 Suite 6-401
 Indianapolis, IN 46204
 Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name in use and whether there is any infringement of patents is the sole responsibility of the user.

All trademarks are owned by one or more affiliates within the Calumet, Inc. organization, unless otherwise specified.

© 2026 Calumet, Inc.

4/30/2026