

Gear Saver Transmission Oil

PRODUCT DESCRIPTION

Bel-Ray® Gear Saver Transmission Oil, a premium petroleum transmission and gear oil, is specifically formulated for all transmissions with wet clutches. It offers superior gear and bearing protection while maximizing clutch performance.

Gear Saver Transmission Oil is a premium transmission oil specifically formulated for wet clutch transmissions. Gear Saver Transmission Oil provides maximum gear and bearing protection and smooth clutch performance for the most demanding off-road racing. The premium petroleum base oils ensure exceptional shear stability and oxidation resistance for long lasting performance and extended drain intervals. Anti-foam and anti-oxidant properties ensure the most effective lubrication and gear protection.



PRODUCT FEATURES

- Extreme Pressure and anti-wear
- Low friction
- Shear stable viscosity
- Better clutch performance

BENEFITS

- Eliminates wear by chemically bonding to gear wear areas. Prevents metal-to-metal contact caused by heavy shock loads during on/off throttle operation
- Special lubricity additives cling to metal surfaces reducing internal friction. High film strength and reduced film thickness lower internal drag and heat build-up
- Prevents viscosity loss due to shear
- Meets the frictional requirements for improved grip and smooth power transfer without clutch slippage or grabbing for consistent hole-shot performance

APPLICATIONS

- For all transmissions with wet clutches
- Equally suitable for gear or chain primary drive

DISTRIBUTED BY:

Calumet Branded Products, LLC
1060 N Capitol Ave
Suite 6-401
Indianapolis, IN 46204
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name in use and whether there is any infringement of patents is the sole responsibility of the user.

All trademarks are owned by one or more affiliates within the Calumet, Inc. organization, unless otherwise specified.

© 2026 Calumet, Inc.

7/24/2026

TECHNICAL DATA SHEET



PRODUCT DATA

Typical Properties			
Property	Test Method	75W	80W
Density @ 15°C (g/mL)	ASTM D4052	0.8571	0.8691
Viscosity @ 40°C (cSt)	ASTM D445	29.84	57.6
Viscosity @ 100°C (cSt)	ASTM D445	5.54	9.53
Viscosity Index	ASTM D2270	126	150
Flash Point, °C (°F)	ASTM D92	224 (430)	232 (450)
Pour Point, °C (°F)	ASTM D97	-48 (-54)	-45 (-49)
Brookfield Viscosity, cP	ASTM D2983	16,236 @ -40°C	8,338 @ -26°C
Copper Corrosion, 3 h @ 100°C (Rating)	ASTM D130	1b	1b

HEALTH and SAFETY

Health and safety recommendations for products can be found on the Safety Data Sheet (SDS) at www.belray.com

DISTRIBUTED BY:

Calumet Branded Products, LLC
1060 N Capitol Ave
Suite 6-401
Indianapolis, IN 46204
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name in use and whether there is any infringement of patents is the sole responsibility of the user.

All trademarks are owned by one or more affiliates within the Calumet, Inc. organization, unless otherwise specified.

© 2026 Calumet, Inc.

7/24/2026